

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

NAK1-BP44

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR

09/889473

INTERNATIONAL APPLICATION NO.

PCT/JP00/00281

INTERNATIONAL FILING DATE

January 21, 2000

PRIORITY DATE CLAIMED

January 22, 1999

TITLE OF INVENTION

GAS DISCHARGE PANEL, GAS DISCHARGE DEVICE, AND RELATED METHODS OF MANUFACTURE

APPLICANT(S) FOR DO/EO/US

Ryuichi Mural et al.

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (24) indicated below.
4. ☐ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371 (c) (2))
 - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
 - a. ☒ is attached hereto.
 - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☒ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).
10. ☐ An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).
11. ☒ A copy of the International Preliminary Examination Report (PCT/IPEA/409).
12. ☒ A copy of the International Search Report (PCT/ISA/210).

Items 13 to 20 below concern document(s) or information included:

13. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
14. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
15. ☒ A **FIRST** preliminary amendment.
16. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
17. ☐ A substitute specification.
18. ☐ A change of power of attorney and/or address letter.
19. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
20. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
21. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
22. ☒ Certificate of Mailing by Express Mail
23. ☒ Other items or information:

PCT Request, Copy of International Publication

U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR 09/889473)		INTERNATIONAL APPLICATION NO. PCT/JP00/00281		ATTORNEY'S DOCKET NUMBER NAKI-BP44	
--	--	--	--	--	--

24. The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) : <input type="checkbox"/> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$1000.00 <input checked="" type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$860.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$710.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$690.00 <input type="checkbox"/> International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00				CALCULATIONS PTO USE ONLY <div style="border: 1px solid black; height: 100px; width: 100%;"></div>	
ENTER APPROPRIATE BASIC FEE AMOUNT =				\$860.00	
Surcharge of \$130.00 for furnishing the oath or declaration later than months from the earliest claimed priority date (37 CFR 1.492 (e)). <input type="checkbox"/> 20 <input type="checkbox"/> 30				\$0.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	43 - 20 =	23	x \$18.00	\$414.00	
Independent claims	8 - 3 =	5	x \$80.00	\$400.00	
Multiple Dependent Claims (check if applicable). <input type="checkbox"/>				\$0.00	
TOTAL OF ABOVE CALCULATIONS =				\$1,674.00	
<input checked="" type="checkbox"/> Applicant claims small entity status. (See 37 CFR 1.27). The fees indicated above are reduced by 1/2.				\$0.00	
SUBTOTAL =				\$1,674.00	
Processing fee of \$130.00 for furnishing the English translation later than months from the earliest claimed priority date (37 CFR 1.492 (f)). <input type="checkbox"/> 20 <input type="checkbox"/> 30 +				\$0.00	
TOTAL NATIONAL FEE =				\$1,674.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). <input checked="" type="checkbox"/>				\$40.00	
TOTAL FEES ENCLOSED =				\$1,714.00	
				Amount to be: refunded	\$
				charged	\$

a. ☒ A check in the amount of **\$1,714.00** to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. _____ in the amount of _____ to cover the above fees. A duplicate copy of this sheet is enclosed.


c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. **16-2462**. A duplicate copy of this sheet is enclosed.

d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. **Credit card information should not be included on this form.** Provide credit card information and authorization on PTO-2038.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Joseph W. Price
 PRICE AND GESS
 2100 S.E. Main St., Ste. 250
 Irvine, CA 92614
 Tel: 949/261-8433


 SIGNATURE
 Joseph W. Price
 NAME
 25,124
 REGISTRATION NUMBER
 July 17, 2001
 DATE

NAK1-BP44

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Ryuichi Murai et al.

Serial No.:

Filed:

For: GAS DISCHARGE PANEL, GAS
DISCHARGE DEVICE, AND RELATED
METHODS OF MANUFACTURE

Examiner:

Group Art Unit:

July 17, 2001

Irvine, California 92614

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

Prior to an examination on the merits of the above-identified application, please enter the following amendments:

IN THE ABSTRACT OF THE DISCLOSURE:

Enclosed is an Abstract of the Disclosure.

IN THE CLAIMS:

Please amend the claims as follows:

1 1. (Amended) A gas discharge panel having (a) a plurality of cells arranged in a
2 matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of
3 substrates and a plurality of barrier ribs interposed between the pair of substrates, and (b) plural
4 pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in
5 a row direction of the matrix, wherein image display is generated by a discharge fired between
6 the plural pairs of display electrodes, each pair of display electrodes comprising:

7 two bus lines, being parallel to each other and extending in the row direction of the
8 matrix;

9 one or more inner protrusions, being arranged within each cell on an inner side of one or
10 both of the bus lines so as to protrude toward an inner side of an opposite bus line; and

11 one or more outer protrusions, being arranged so as to protrude from an outer side of one
12 or both of the bus lines, at least a section of each of the inner and outer protrusions being
13 positioned between two adjacent barrier ribs.

14 10. (Amended) The gas discharge panel of claim 1, wherein the inner protrusions are
15 provided on each of the two bus lines, the ends of the inner protrusions arranged on each of the
16 bus lines being out of alignment along the row direction of the matrix, and the outer protrusions
17 being arranged so that the discharge fired between the plural pairs of display electrodes expands
18 from the inner protrusions to the outer protrusions.

19 21. (Amended) A gas discharge panel having (a) a plurality of cells arranged in a
20 matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of
21 substrates and a plurality of barrier ribs interposed between the pair of substrates, and (b) plural
22 pairs of display electrodes composed of a metal and arranged on an inner surface of one of the

substrates so as to extend in a row direction of the matrix, wherein image display is generated by a discharge fired between the plural pairs of display electrodes, each pair of display electrodes comprising:

two bases, being parallel to each other and extending in the row direction of the matrix; and

one or more inner protrusions, being arranged within each cell on an inner side of each of the bases so as to protrude toward an inner side of an opposite base, the ends of the inner protrusions arranged on each of the bases being out of alignment along the row direction of the matrix.

28. (Amended) A gas discharge panel having (a) a plurality of cells arranged in a matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of substrates and a plurality of barrier ribs interposed between the pair of substrates, and (b) plural pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix, each pair of display electrodes comprising:

two bases, being extended in a row direction of the matrix and snaking along the plural pairs of display electrodes.

33. (Amended) A gas discharge panel having (a) a plurality of cells arranged in a matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of substrates and a plurality of barrier ribs interposed between the pair of substrates, and (b) plural pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix, each pair of display electrodes comprising:

two bus lines, being extended in a row direction of the matrix; and

7 two bases, being connected electrically to and snaking along the bus lines, at least a
8 section of the bases being arranged so as to be separate between two adjacent barrier ribs.

Please add the following newly-drafted Claims 42 and 43.

1 42. (New) The gas discharge panel of claim 3, wherein the bus lines are composed of
2 silver.

1 43. (New) The gas discharge panel of Claim 10, wherein the outer protrusions form a
2 whole through the bus line with the inner protrusions.

102720 2268850


REMARKS

The amendments to the claims and newly drafted Claims 42 and 43 are in accordance with a Rule 19 Amendment submitted during the prosecution of the International Application. They are within the scope of the original invention and do not add any new subject matter.

If the Examiner believes that a telephone interview will help further the prosecution of this case, he is respectfully requested to contact the undersigned attorney at the listed telephone number.

Very truly yours,

PRICE AND GESS



Joseph W. Price, Reg. 251,24
2100 S.E. Main St., Ste. 250
Irvine, CA 92614
949/261-8433

VERSION WITH MARKINGS TO SHOW CHANGES MADE

An Abstract of the Disclosure is attached.

The claims have been amended as follows:

1. (Amended) A gas discharge panel having (a) a plurality of cells arranged in a matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of substrates and a plurality of barrier ribs interposed between the pair of substrates, and (b) plural pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix, wherein image display is generated by a discharge fired between the plural pairs of display electrodes, each pair of display electrodes comprising:

two bus lines, being parallel to each other and extending in the row direction of the matrix;

one or more inner protrusions, being arranged within each cell on an inner side of one or both of the bus lines so as to protrude toward an inner side of an opposite bus line; and

one or more outer protrusions, being arranged so as to protrude from an outer side of one or both of the bus lines, at least a section of each of the inner and outer protrusions being positioned between two adjacent barrier ribs.

10. (Amended) The gas discharge panel of claim 1, wherein the inner protrusions are provided on each of the two bus lines, the ends of the inner protrusions arranged on each of the bus lines being out of alignment along the row direction of the matrix, and the outer protrusions being arranged so that the discharge fired between the plural pairs of display electrodes expands from the inner protrusions to the outer protrusions.

1 21. (Amended) A gas discharge panel having (a) a plurality of cells arranged in a
2 matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of
3 substrates and a plurality of barrier ribs interposed between the pair of substrates, and (b) plural
4 pairs of display electrodes composed of a metal and arranged on an inner surface of one of the
5 substrates so as to extend in a row direction of the matrix, wherein image display is generated by
6 a discharge fired between the plural pairs of display electrodes, each pair of display electrodes
7 comprising:

8 two bases, being parallel to each other and extending in the row direction of the matrix;

9 and

10 one or more inner protrusions, being arranged within each cell on an inner side of each of
11 the bases so as to protrude toward an inner side of an opposite base, the ends of the inner
12 protrusions arranged on each of the bases being out of alignment along the row direction of the
13 matrix.

1 28. (Amended) A gas discharge panel having (a) a plurality of cells arranged in a
2 matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of
3 substrates and a plurality of barrier ribs interposed between the pair of substrates, and (b) plural
4 pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in
5 a row direction of the matrix, each pair of display electrodes comprising:

6 two bases, being extended in a row direction of the matrix and snaking along the plural
7 pairs of display electrodes.

1 33. (Amended) A gas discharge panel having (a) a plurality of cells arranged in a
2 matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of

3 substrates and a plurality of barrier ribs interposed between the pair of substrates, and (b) plural
4 pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in
5 a row direction of the matrix, each pair of display electrodes comprising:
6 two bus lines, being extended in a row direction of the matrix; and
7 two bases, being connected electrically to and snaking along the bus lines, at least a
8 section of the bases being arranged so as to be separate between two adjacent barrier ribs.

Claims 42 and 43 have been added.

0000473-071701

24 PAGES

GAS DISCHARGE PANEL, GAS DISCHARGE DEVICE, AND RELATED METHODS
OF MANUFACTURE

TECHNICAL FIELD

The present invention relates generally to a gas discharge panel and a gas display device used for TV displays and the like, and more particularly to a plasma display panel (PDP).

BACKGROUND ART

The demand in recent years for wide-screen displays with an image quality typified by high-vision has seen much research directed into cathode ray tube (CRT), liquid crystal display (LCD), and plasma display panel (PDP) technologies. CRTs are widely used in televisions and the like for their high resolution and image quality, although the large increases in device depth and weight that accompany increases in screen size mean that CRTs having a diagonal screen size exceeding 40 inches are not considered feasible.

LCDs by far exceed CRTs in terms of reduced energy consumption, device depth, and weight, and are now widely used as computer monitors, although the intricate construction of thin film transistors (TFT), the most common type of LCD, means that the manufacturing process is very involved. Increases in

screen size consequently lead to a drop in yield rates, making the manufacture of LCDs over 20 inches not as yet feasible.

The attraction of PDPs, on the other hand, is the ability to combine a wide screen with a comparatively lightweight display. Increasing the screen size of PDPs has thus been a focus in the push to develop the displays of the future, and already available on the market are products having a diagonal screen size in excess of 60 inches.

PDPs are a type of gas discharge panel comprising two facing glass substrates, the inner surface of one of the glass substrates including plural pairs of display electrodes arranged in strips across a plurality of barrier ribs. Phosphors corresponding to the colors red, green, and blue are applied in order in the gap between adjacent barrier ribs, one color per gap, respectively, and the space between the two glass substrates is sealed. Phosphor illumination is then generated by discharging ultraviolet light (UV) within the discharge space, which is the sealed space between the two glass substrates and the interposed barrier ribs.

Direct current (DC) and alternating current (AC) are the two types of PDPs, distinguished by the power source used to drive them. AC PDPs, generally recognized as the most suitable for wide-screen application, are fast becoming the norm.

Due to contemporary demands for energy efficient

00009473-071701

electrical appliances, much of the interest in PDP development has centered on reducing the energy taken to drive them. This focus is particularly emphasized given the rise in energy consumption resulting from recent trends toward developing PDPs with larger screens and higher image definition.

One means of reducing the energy consumption of PDPs is to improve the illuminance efficiency, although measures that simply aim to cut the electricity supplied to PDPs are not viable because of resultant drops in illumination and display capacity caused by a reduction in the discharge capacity generated between the pairs of display electrodes. Improving the rate at which the phosphors change ultraviolet light into visible light is one way in which improvements in illuminance efficiency are being pursued, although much work still needs to be done in this area.

The issues discussed above relate not only to PDPs and other gas discharge panels but also to gas discharge devices (i.e. devices providing illumination by generating a discharge within a glass vessel filled with a discharge gas). The present difficulties in developing gas discharge panels and gas discharge devices lie, therefore, in securing a favorable discharge capacity while sustaining the illuminance efficiency.

DISCLOSURE OF INVENTION

In response to the above issues, the present invention seeks to provide (a) a gas discharge panel and a gas discharge device that secure a favorable discharge capacity while sustaining the illuminance efficiency, and (b) the related methods of manufacture.

The above objectives are to be achieved by a gas discharge panel having (a) a plurality of cells arranged in a matrix, each of the cells being filled with a discharge gas enclosed between a pair of substrates, and (b) pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix. Each pair of display electrodes comprise (a) two bus lines lying parallel to each other and extending in the row direction of the matrix, (b) one or more inner protrusions arranged within each cell on an inner side of one or both of the bus lines so as to protrude toward an inner side of an opposite bus line, and (c) one or more outer protrusions arranged so as to protrude from an outer side of one or both of the bus lines.

According to the above construction, a shortest gap (discharge gap) between each pair of display electrodes is either the gap between one of the bus lines and the inner protrusions provided on the opposite bus line or the gap between the inner protrusions provided on both of the bus lines.

Discharge is generated in the shortest gap. By concentrating the electric charge within the shortest gap during the discharge period, it is possible to keep the discharge firing voltage below existing levels. Also, the generated discharge gradually expands to the outer protrusions, allowing a sustain discharge (surface discharge) to be secured over a wide area. Thus the present invention allows for an excellent discharge capacity to be achieved while improving the illuminance efficiency above existing levels. According to the present invention, it is also possible to arrange the inner protrusions on each of the bus lines so that the ends are out of alignment along the row direction of the matrix.

In summary, the excellent discharge capacity and improved illuminance efficiency achieved by the present invention are due to the favorable way in which the discharge capacity expands along the row and column directions of the matrix (i.e. parallel to the surface of the substrates) at the time of sustaining the discharge between the pairs of display electrodes.

BRIEF DESCRIPTION OF DRAWINGS

Fig.1 is a cross-sectional perspective view of a section of the PDP of the first embodiment;
Fig.2 is a schematic view of the panel driving part, the display electrodes, and so on, of the first embodiment;

Fig.3 shows the driving process of the panel driving part of the first embodiment;

Fig.4 is a frontal illustration of the display electrodes of the PDP of the first embodiment;

Fig.5 is a frontal illustration of a variation of the display electrodes (variation 1-1) of the first embodiment;

Fig.6 is a frontal illustration of a variation of the display electrodes (variation 1-2) of the first embodiment;

Fig.7 is a frontal illustration of a variation of the display electrodes (variation 1-3) of the first embodiment;

Fig.8 is a frontal illustration of a variation of the display electrodes (variation 1-4) of the first embodiment;

(a) is a frontal illustration of a variation of the display electrodes (variation 1-4) of the first embodiment;

(b) is a frontal illustration of a variation of the display electrodes (variation 1-5) of the first embodiment;

(c) is a frontal illustration of a variation of the display electrodes (variation 1-6) of the first embodiment;

(d) is a frontal illustration of a variation of the display electrodes (variation 1-7) of the first embodiment;

(e) is a frontal illustration of a variation of the display electrodes (variation 1-8) of the first embodiment;

(f) is a frontal illustration of a variation of the display electrodes (variation 1-9) of the first embodiment;

Fig.9 is a frontal illustration of a variation of the display electrodes (variation 1-10) of the first embodiment;

Fig.10 is a frontal illustration of a variation of the display electrodes (variation 1-11) of the first embodiment;

Fig.11 is a frontal illustration of a variation of the display electrodes (variation 1-12) of the first embodiment;

Fig.12 is a frontal illustration of the display electrodes of the PDP of the second embodiment;

Fig.13 is an enlarged partial view of the display electrodes of the second embodiment;

Fig.14 is a frontal illustration of a variation of the display electrodes (variation 2-1) of the second embodiment;

Fig.15 is a frontal illustration of a variation of the display electrodes (variation 2-2) of the second embodiment;

Fig.16 is a frontal illustration of a variation of the display electrodes (variation 2-3) of the second embodiment;

Fig.17 is a frontal illustration of a variation of the display electrodes (variation 2-4) of the second embodiment;

(a) is a frontal illustration of a variation of the display electrodes (variation 2-4) of the first embodiment;

(b) is a frontal illustration of a variation of the display electrodes (variation 2-5) of the first embodiment;

(c) is a frontal illustration of a variation of the display electrodes (variation 2-6) of the second embodiment;

(a) is a perspective view of a section of the display electrodes of an existing PDP;

(b) is a frontal illustration of the display electrodes of an existing PDP.

BEST MODE FOR CARRYING OUT THE INVENTION

<First Embodiment>

Fig.1 is a cross-sectional perspective view showing a principal construction of an AC PDP module (hereafter "PDP 2") of a PDP display apparatus, being an example gas discharge apparatus of the first embodiment. In Fig.1, the PDP 2 is thick in a z direction and the surface of the PDP 2 runs parallel to the xy plane. This description applies to all the figures discussed below. The PDP display apparatus of the first embodiment is divided broadly into the PDP 2 and the panel driving part 1 described below. The construction of a panel driving part 1 is the same with respect to the first, second, and third embodiments, and to each of the variations 1-1~1-12 and 2-1~2-13.

As shown in Fig.1, the PDP 2 is formed by a front panel 20 and a back panel 26 arranged so as to face each other. A front panel glass 21 forming the substrate of the front panel 20 is arranged on one side with plural pairs of display electrodes 22 and 23 (Y electrode 22, X electrode 23) running parallel in

the x direction, surface discharge being conducted between each pair of display electrodes 22 and 23. A detailed explanation of the display electrodes 22 and 23 is given below. The entire surface of the front panel glass 21 arranged with display electrodes 22 and 23 is covered with a dielectric layer 24, and the dielectric layer 24 is then covered in turn with an insulating layer 25.

One side of a back panel glass 27 forming the substrate of the back panel 26 is provided, in evenly spaced strips, with a plurality of address electrodes 28 arranged so as to extend in the y direction. The entire surface of the back panel glass 27 is then covered with a dielectric film 29, covering over the address electrodes 28. Barrier ribs 30 are arranged in the space between adjacent address electrodes 28, and phosphor layers 31~33 corresponding to the colors red (R), green (G), and blue (B) are formed on the sides of adjacent barrier ribs 30 and the surface of the dielectric film 29 lying between adjacent barrier ribs. The RGB phosphor layers 31~33 are arranged serially in the x direction. This completes the process for enabling image display to be generated on the PDP 2.

The front panel 20 and back panel 26 face each other so that the display electrodes 22 and 23 lie orthogonally to the address electrodes 28, the periphery of both panels 20 and 26 coming into contact and being sealed. A discharge gas (enclosed

173nm) is generated. The phosphor layers 31~33 are thus illuminated and image display is generated.

Fig.2 is a schematic view of the front panel glass 21 arranged with display electrodes 22 and 23, and the panel driving part 1 connected to both the display electrodes 22 and 23 and the address electrodes 28. The panel driving part 1 shown in Fig.2 has a common construction comprising a data driver 101 connected to the address electrodes 28, a sustain driver 102 connected to each of the Y electrodes 22, a scan driver 103 connected to each of the X electrodes 23, and a driving circuit 100 controlling the drivers 101~103. Each of the drivers 101~103 control the flow of electricity to each of the electrodes 22, 23, and 28, connected respectively, and the driving circuit 100 forms an umbrella controlling the drivers 101~103 so as to generate a favorable image display on the PDP 2.

The basic process by which the panel driving part 1, comprising the above construction 100~104, drives the PDP 2 will now be explained with reference to the pulse wave diagram in Fig.3. First, the panel driving part 1 applies an initializing pulse via the scan driver 103 to each of the X electrodes 23 and initializes an electric charge (wall electric charge) existing within each of the cells 340. Via the scan driver 103 and the data driver 101, the panel driving part 1 then simultaneously applies a scan pulse to the X electrode 23

0000473.071701
102720.246880

positioned at the top of the panel and a rewriting pulse to the address electrodes 28 corresponding to the cells 340 contributing to image display, thus generating a rewriting discharge and storing wall electric charge on the surface of the dielectric layer 24.

Next, via the scan driver 103 and the data driver 101, the panel driving part 1 simultaneously applies a scan pulse to the X electrode 23 positioned second from the top of the panel and a rewriting pulse to the address electrodes 28 corresponding to the cells 340 contributing to image display, thus generating a rewriting discharge and storing wall electric charge on the surface of the dielectric layer 24.

By applying a continuous scan pulse, the panel driving part 1 continues, in the above manner, to serially store, on the surface of the dielectric layer 24, a wall electric charge corresponding to the cells 340 contributing to image display, and thus rewrite the latent image of each screen image of the PDP 2.

The panel driving part 1 then grounds the address electrodes 28 and applies a sustain pulse via the scan driver 103 and the sustain driver 102 to all of the display electrodes 22 and 23 in isolation so as to generate a sustain discharge (surface discharge). As a result of the electric potential of the surface of the dielectric layer 24 exceeding the discharge

firing voltage, discharge is generated within the cells 340 having wall electric charge stored on the surface of the dielectric layer 24, and the discharge (surface discharge) is sustained for the period that the sustain pulse is applied (the discharge sustaining period shown in Fig.3).

Then, via the scan driver 103, the panel driving part 1 applies a narrow pulse to the X electrodes 23, thereby generating an imperfect discharge and eliminating the wall electric charge. Deletion of the screen image follows (deletion period). The panel driving part 1 generates image display on the PDP 2 through a repetition of this process.

The structure of the panel driving part 1 of the PDP display apparatus and the entire PDP 2, as well as their basic functions have been described above. The characteristics of the first embodiment relate mainly to the display electrodes 22 and 23.

Fig.4 is a frontal illustration of a section of the front panel of the PDP 2 as viewed from the z direction (i.e. from above the PDP). In Fig.4, the area of the cells 340 is the area marked out within the broken lines. The cell pitch in the x direction (P_x) and y direction is $360 \mu m$ and $1080 \mu m$, respectively, and one square pixel ($1080 \mu m \times 1080 \mu m$) corresponding to the colors RGB is formed by any three cells 340 lying next to each other in the x direction. In the interest

of simplification, the address electrodes 28 have not been shown in Fig.4 through Fig.21.

As shown in Fig.4, each pair of display electrodes 22 and 23 (Y electrodes 22, X electrodes 23) comprise bus electrodes (bus lines) 221 and 231 formed from metal strips $40\mu\text{m}$ wide and extending in the x direction, and isolated rectangular-shaped electrodes 222 and 232 extending in the y direction. According to the given example, the gap D_2 between each pair of adjacent bus lines is $90\mu\text{m}$.

The isolated electrodes 222 and 232 are composed of indium tin oxide (ITO), which is a material commonly used for transparent electrodes, and according to the given example, the isolated electrodes 222 and 232 have a length (y direction) and width (x direction) of $135\mu\text{m}$ and $40\mu\text{m}$, respectively, and a thickness (z direction) of $0.1\sim 0.2\mu\text{m}$. The isolated electrodes 222 and 232 are arranged on each of the bus lines 221 and 231 so that, within each of the cells 340, two isolated electrodes 222 and 232 are provided on each of the bus line 221 and 231 along the x direction. The isolated electrodes 222 and 232 are arranged so as to be opposed to each other.

The isolated electrodes 222 and 232 provided along each of the bus lines 221 and 231 are arranged so that a pitch (P_e) of two isolated electrodes 222 and 232 adjacent in the x direction is smaller than a cell pitch (P_s). Specifically, the

222a and 232a and outer protrusions 222b and 232b. According to the present example, the length of the inner protrusions 222a and 232a and the outer protrusions 222b and 232b in the y direction is $30\mu\text{m}$ and $75\mu\text{m}$, respectively.

While the isolated electrodes 222 and 232 according to the first embodiment are provided along each of the bus lines 221 and 231, this construction is simply for ease of manufacture. Thus it is possible to arrange the inner protrusions 222a and 232a and the outer protrusions 222b and 232b separately, without it being necessary to provide the isolated electrodes 222 and 232.

A gap D_1 between the inner protrusions 222a and 232a is determined according to Paschen's Law. Specifically, at the discharge gas pressure mentioned above ($266 \times 10^3 \text{Pa}$), the gap D_1 at the minimum discharge firing voltage or a voltage in the near vicinity thereof is set at $30\mu\text{m}$ as represented on a Paschen curve plotting the relationship between a Pd product and the pressure of the discharge gas, where P is the pressure of the discharge gas and d is the discharge gap. So as to achieve a sufficient sustain discharge capacity, the maximum gap D_3 between the isolated electrodes 222 and 232 is set at $300\mu\text{m}$.

The gap D_1 in Fig.4 has been shown wider than in actuality so as to clearly represent the relationship between the isolated

electrodes 222 and 232. Although not shown, a sufficient gap has also being provided between the outer protrusions 222b and 232b and adjacent cells 340 in the y direction so as to prevent the occurrence of cross talk (this gap being in the 150~200 μm range, for example).

In a PDP display apparatus having the PDP 2 described above, surface discharge is fired within the discharge gap D_1 , which exists between the tips of two facing inner protrusions 222a and 232a and which is determined according Paschen's Law, when a feed pulse is applied to the display electrodes 22 and 23 during the discharge period. As shown in Fig.24, existing constructions of the display electrodes 22 and 23 have commonly comprised bus lines 221 and 231 and transparent electrodes 220 and 230 extending in the x direction and having a width (in the y direction) of 50 μm or greater. When the isolated electrodes 222 and 232 are provided according to the first embodiment of the present invention, however, the voltage (discharge firing voltage) needed to generate the discharge can be kept at a lower level than is the case with existing constructions. Thus a favorable firing discharge is obtained while keeping energy consumption below existing levels.

A surface area of the display electrodes 22 and 23 contributing to the discharge expands to the outer side of the parallel bus lines 221 and 231 when the discharged has been fired

09889473-071701

and is being sustained. In other words, the discharge generated within the discharge gap D_1 expands elliptically from the area of the discharge gap D_1 (i.e. the discharge expands elliptically along the y direction) until it reaches the outer protrusions 222b and 232b. Thus it is possible to secure a discharge capacity contributing to the illumination of cells 340 over a wide area.

Existing constructions of the display electrodes 22 and 23 (Fig.24) tend to use excess electricity in the vicinity of the barrier ribs 30 for illuminating the cells 340 when band-shaped transparent electrodes 220 and 230 are provided. In comparison, energy savings are possible according to the first embodiment of the present invention because the use of a transparent electrode material for forming the isolated electrodes 222 and 232 is limited to areas that contribute effectively to illuminating the cells 340. The amount of electricity needed for discharging the display electrodes 22 and 23 can, therefore, be reduced.

While Japanese unexamined patent application publications no.8-250029 and no.11-86739, and U.S. patent no.5587624 disclose a display electrode construction having protrusions, they only disclose for a construction having either inner protrusions or outer protrusions on each pair of bus lines. This existing technology not only differs from the first embodiment of the present invention but it does not allow

for the expansion, via the outer protrusions, of the discharge capacity to the outer side of the parallel bus lines nor for the reduction of the discharge firing voltage applied to the inner protrusions.

Also, while Japanese unexamined patent application publication no.5-266801 discloses technology for conducting a plurality of boring processes in band-shaped transparent electrodes, the bored sections are for attaching the bus lines to the front panel glass, and any reduction in transparent electrode material is not sufficient to be considered an energy saving measure. Consequently, it is not possible for the effects of the first embodiment of the present invention to be gained from this existing technology.

Although not described in detail here, improved illuminance efficiency was recorded under experiment conditions when the width of the isolated electrodes was reduced from $40\mu\text{m}$ to $20\mu\text{m}$ and two protrusions were provided within each of the cells. Such adjustments are possible according to the first embodiment.

All of the variations of the first embodiment will now be described. Redundant description has been omitted since all significant alteration to the construction described in the first embodiment relate to the display electrodes 22 and 23.

<Variation 1-1>

Effective reductions in the discharge firing voltage can be achieved by concentrating the electric charge (i.e. by increasing the intensity of the electric field) in the area of the display electrodes (the inner protrusions 222a and 232a) contributing to the firing during the discharge period. Fig.5 (variation 1-1) is a frontal illustration of display electrodes formed in this way. As shown in Fig.5, the tips of the inner protrusions 222a and 232a have been rounded, reducing the surface area. This construction allows for further reductions in the discharge firing voltage because of the favorable way in which the electric charge is concentrated and the resultant easy firing of the discharge.

<Variation 1-2>

Outer protrusions 222b and 232b need only be provided on one rather than both of the display electrodes 22 and 23. Variation 1-2 shown in Fig.6 has display electrodes formed in this manner. In variation 1-2, only the outer protrusions 232b are provided. It is also possible to provide only the outer protrusions 222b instead. Discharge capacity is secured by the outer protrusions 232b during the discharge period when they are the only outer protrusions provided.

By arranging outer protrusions (either 222b or 232b) on

only one of the display electrodes (either 22 or 23, respectively) it is possible to decrease the maximum distance D_3 between the display electrodes 22 and 23. Thus variation 1-2 provides a construction applicable, for instance, in high-vision televisions having a high definition of cells 340. To further improve the illuminance efficiency of the sustain discharge, the number of outer protrusions 222b or 232b can be increased and the surface area of the outer protrusions 222b or 232b can be made larger than that of the inner protrusions 222a and 232a.

<Variation 1-3>

The inner protrusions 222a and 232a of the first embodiment need only be arranged on one rather than both of the display electrodes 22 and 23. Variation 1-2 shown in Fig.7 has display electrodes formed in this manner. In variation 1-2, only the inner protrusions 232a are provided and the total number of outer protrusions 222b and 232b arranged within each of cells 340 is four.

It is possible to provide only the outer protrusions 222a instead and to increase the number of the outer protrusions 222b and 232b. Because the inner protrusions 222a are fewer than the outer protrusions 222b and 232b according to this construction, it is possible to reduce the amount of electricity concentrated

in the area of the inner protrusions 222a during the discharge period. It is also possible to achieve a sustain discharge across a wide area because of the comparatively wide discharge area secured by the large number of outer protrusions 222b and 232b. The discharge gap D_2 and D_3 can also be decreased since the inner protrusions 222a are the only inner protrusions provided in variation 1-3. As with variation 1-2, variation 1-3 provides a construction that is compatible with a high definition of cells 340.

<Variation 1-4~1-9>

Figs.8(a)~(f) show variations 1-4~1-9, respectively, of the first embodiment. In variation 1-4 shown in Fig.8(a), each of the outer protrusions 222b and 232b are divided into three electrode arms, the pitch (i.e. in an x direction) of the three arms being wider as the distance from the bus line increases. By allowing for the smooth expansion of the discharge capacity, this construction helps reduce the discharge firing voltage and improves the ability to sustain the discharge capacity. The same effect can be gained from the isolated triangular electrodes 222 and 232 of variation 1-5 shown in Fig.8(b) and the isolated array-shaped electrodes 222 and 232 of variation 1-9 shown in Fig.8(f) (the inner protrusions 222a and 232b being smaller than the outer protrusions 222b and 232b). Variation 1-7 shown in

Fig.8(d) effectively reduces the discharge firing voltage by concentrating the electric charge in the area of the inner electrodes 222a and 232a. When the ends of the inner protrusions 222a and 232a are shaped like a fork, the reduced volume and surface area of the inner protrusions 222a and 232a makes it possible to concentrate the electric charge more effectively. Variation 1-8 shown in Fig.8(e) strikes a balance between reducing the discharge firing voltage and improving the illuminance efficiency by providing inner protrusions 222a and 232a with fork-shaped ends and outer protrusions 222b and 232b that are wider in the x direction as the distance from the bus line increases.

According to the first embodiment, it is also possible for the electrode arms of the outer protrusions 222b and 232b to be joined in the x direction. The construction of variation 1-7 shown in Fig.8(c) is such that the arms of two adjacent outer electrodes 222b and 232b are joined.

<Variation 1-10~1-12>

The first embodiment is not limited to the example constructions given in the first embodiment and the variations 1-1~1-9 in which the display electrodes 22 and 23 comprise bus lines 221 and 231 and isolated electrodes 222 and 232 (inner protrusions 222a and 232b, outer protrusions 222b and 232b).

In variation 1-10 shown in Fig.9, the display electrodes 22 and 23 comprise bus lines 221 and 231 and transparent electrodes 220 and 230 (snaking electrodes 220 and 230), extending symmetrically in an x direction and snaking in a y direction. The tendency with variation 1-10 is for electricity consumption to increase slightly in comparison to when isolated electrodes 222 and 232 are provided, although this construction does allow for the discharge capacity to be secured over a wider area.

In variation 1-10, the snaking electrodes 220 and 230 on the inner and outer side of the bus lines 221 and 231 are the inner protrusions 222a and 232a and outer protrusions 222b and 232b, respectively. The width of the snaking electrodes 220 and 230 is 20~30 μm in the given example. In variation 1-10, the discharge generated at the ends of the inner protrusions 222a and 232a during the driving period of the PDP 2 expands to the outer protrusions 222b and 232b. This effect is comparable to that gained in the first embodiment and with variations 1-1 and 1-9 (i.e. a favorable reduction in discharge firing voltage and securing of discharge capacity during the discharge period). For there to be a comparable number of inner protrusions 222a and 232a and outer protrusions 222b and 232b as the first embodiment, it is necessary for the snaking electrodes 220 and 230 to have at least 2 to 3 peaks within each of the cells 340.

It is also possible to have the snaking electrodes 220 and 230 stand separately within each of the cells 340. In variation 1-11 shown in Fig.10, the section of the snaking electrodes 220 and 230 that overlapped with the barrier walls has been eliminated and the remaining section stands separately within each of the cells 340. According to this construction it is possible to further reduce the amount of electricity applied to the snaking electrodes 220 and 230 in comparison to variation 1-10.

In variation 1-12 shown in Fig.11, the display electrodes 22 and 23 are snaking electrodes composed only of a metal. Although variation 1-12 maintains a construction providing inner protrusions 222a and 232a and outer protrusions 222b and 232b, the non-use of transparent electrode material makes it possible to realize large reductions in the electricity applied to the display electrodes 22 and 23.

<Second Embodiment>

Fig.12 is a frontal illustration of the display electrodes of the PDP 2 of the second embodiment. Fig.12 shows a construction having only one isolated electrode arranged on each of the bus lines 221 and 231 within each cell 340. It is, however, possible to arrange two isolated electrodes per cell, as in the first embodiment, in which case it is desirable to

09880473-071701

arrange the isolated electrodes 222 and 232 to satisfy the relation $P_e = A \times P_s / n$.

In the second embodiment, the isolated electrodes 222 and 232 are arranged, as in the first embodiment, according to Paschen's Law, this time to have a gap (shortest gap D_1) of 40 μm therebetween. As shown in Fig.13, the squared ends of each of the inner protrusions 222a and 232a are out of alignment in the x direction. The inner protrusions 222a and 232a can be arranged, as in Fig.12, so that central lines A and B running in the y direction are out of alignment. The "central lines" referred to here are the lines dividing the surface of the inner protrusions 222a and 232a in half (Fig.12). The reason for having the isolated electrodes 222 and 232 out of alignment with each other will now be discussed.

As shown in the enlarged illustration of the display electrodes in Fig.13, it is possible, during the discharge sustaining period, to have the discharge expand from the shortest gap D_1 along the flat surface of the panel of the PDP 2 (i.e. in both the x and y directions, the direction of the discharge in Fig.13 forming the axis). In a PDP display apparatus have the above construction, the electric charge is concentrated close to the inner electrodes 222a and 232a when the sustain pulse is applied to the plural pairs of display electrodes 22 and 23, as in the first embodiment. Discharge is

then fired in the gap D_1 using a lower discharge firing voltage then existing technology. As a surface area of the display electrodes 22 and 23 contributing to the discharge gradually spreads to the outer side of the parallel bus lines 221 and 231 during the discharge period, the discharge capacity expands in the x and y directions (along the surface of the panel), as shown in Fig.13.

According to the second embodiment, it is possible to improve the expansion of the discharge capacity, particularly in the x direction, beyond the levels achievable by the first embodiment by arranging the inner protrusions 222a and 232a on each of the bus lines 221 and 231 so as to be out of alignment. The discharge generated in the discharge gap D_1 expands beyond the bus lines 221 and 231 to the largest discharge gap D_3 , and surface discharge is thus conducted over a wide area.

In order to realize the effect of the second embodiment shown in Fig.13 (i.e. reduction of the discharge firing voltage and securing of the discharge capacity) it is necessary to have the isolated electrodes 222 and 232 out of alignment by a distance equal to or greater than a width of thereof, and to arrange the isolated electrodes 222 and 232 so that no part of the squared ends thereof face each other along the x direction. If a section of the squared ends are to face each other, this section should be kept at $10\mu\text{m}$ or below. According to the

221 and 231. This construction is possible according to the second embodiment. The increased number of outer protrusions 222b and 232b helps expand the capacity of the surface discharge over a wide area during the discharge sustaining period.

In variation 2-3 shown in Fig.16, outer protrusions (232b) are only arranged on one of the bus lines (231). This construction therefore allows the size of each of the cells 340 to be reduced, which means that variation 2-3, as with variation 1-3, is able to achieve the excellent illuminance efficiency required, for example, by high-vision television having a high definition of cells.

<Variation 2-4~2-9>

Variations 2-4~2-9 shown in Figs.17(a)~(f), respectively, have the same shaped isolated electrodes 222 and 232 as variations 1-4~1-9 in Figs.8(a)~(f), the difference being that the isolated electrodes 222 and 232 arranged on each of the display electrodes 22 and 23 in Figs.17(a)~(f) are out of alignment with each other, as per the second embodiment. A combination of the effects of variations 1-4~1-9 and the second embodiment can be achieved with variations 2-4~2-9 (i.e. securing a favorable discharge capacity while improving the illuminance efficiency).

<Variation 2-10>

In variation 2-10 shown in Fig.18, the isolated electrodes 222 and 232 arranged on each of the bus lines 221 and 231 differ from each other in shape and size. The width of isolated electrodes 222 are 2.5 times the width of the isolated electrodes 232, and the isolated electrodes 222 and 232 are arranged, as in the first embodiment, so that the squared ends do not face each other. An excellent discharge capacity can be secured according to this construction because of the favorable way in which the surface discharge expands in the x direction during the discharge sustaining period.

<Variation 2-11>

While variation 2-11 shown in Fig.19 maintains the basic construction of variation 2-10, a section of the isolated electrodes 222 or 232 (232 in the given example) is arranged so as to overlap with the barrier ribs 30. This construction aims to make use of an adjacent-surface discharge generated in the vicinity of barrier ribs 30 during the discharge sustaining period.

According to this construction, discharge is initially generated between the inner protrusions 222a and 232a during the discharge period. In addition to the discharge generated between the isolated electrodes 222 and 232, discharge

(referred to as "adjacent-surface discharge") is also generated along the surface (insulating surface) of the barrier ribs 30 at the protrusions 232, which overlap with the barrier ribs 30, during the discharge sustaining period. Combining the adjacent-surface discharge with the surface discharge in the manner of variation 2-11 allows a surface discharge capacity to be achieved over a wide area. The discharge firing voltage can also be kept below existing levels because of the adjacent-surface discharge being fired by an avalanche of field emission-generated secondary electrons. Variation 2-11 thus has excellent energy saving potential. Variation 2-11 is compatible with variation 2-10, as well as other variations.

<Variation 2-12>

Variation 2-12 shown in Fig.20 maintains the basic construction of variation 2-10, although the degree to which the central lines A and B of the isolated electrodes 222 and 232 are out of alignment is reduced. The effect achieved with this construction is comparable to that of the second embodiment shown in Fig.12. The predetermined effect can therefore be achieved irrespective of the degree to which the isolated electrodes 222 and 232 (especially the inner protrusions 222a and 232a) are out of alignment according to the second embodiment.

<Variation 2-13>

Based on the construction of variation 1-10 (Fig.9) of the first embodiment, variation 2-13 shown in Fig.21 has snaking electrodes 220 and 230, the wavelength of which are in phase with one another. In variation 2-13, the discharge is generated in the shortest gap D_1 during the discharge period and gradually expands to the outer protrusions 222b and 232b during the succeeding discharge sustaining period. In variation 2-13, the expansion of the discharge in the x and y directions occurring from the snaking electrodes 220 and 230, which are arranged on each of the bus lines 221 and 231 so as to be out of alignment in the x direction, is comparable to the expansion of discharge shown in Fig.13. Thus it is possible to secure a favorable discharge capacity and improve the illuminance efficiency.

In variation 2-13, it is possible to arrange the snaking electrodes 220 and 230 so as to be slightly more out of alignment (i.e. slightly out of phase). However, having the snaking electrodes 220 and 230 arranged so as to be in phase with each another means that the inner protrusions 222a and 232a provided on each of the bus lines 221 and 231 are evenly distanced from each another and a healthy discharge gap D_1 is maintained, as shown in Fig.21. With this construction it is therefore possible to achieve a favorable discharge capacity as a result of a single

inner protrusion 222a being able to generate discharge with the two closest inner protrusions 232a separated by a uniform distance from the single inner protrusion 222a.

As in variation 1-11 of the first embodiment, it is possible in variation 2-13 to have the snaking electrodes 220 and 230 arranged so as to stand separately within each of the cells 340. Also, as in variation 1-12 of the first embodiment, it is possible to have no bus lines 221 and 231 and for the display electrodes 22 and 23 to be composed of a metal. Variation 2-13 is compatible for use with the third embodiment and the gas discharge device 400, both of which are discussed below.

<Third Embodiment>

The construction of the display electrodes 22 and 23 of the third embodiment is the same as that of the first embodiment (see Fig.4). The characteristics of the third embodiment relate mainly to the construction of the insulating layer 25. Fig.22 is a cross-sectional view of a section of the thickness (in the z direction) of the PDP 2 of the third embodiment.

According to the construction of the PDP 2 shown in Fig.22, an insulating layer 251 of magnesium oxide (MgO) is formed over an area corresponding to the inner protrusions 222a and 232a (i.e. the area directly above the inner protrusions 222a and 232a in Fig.22), and an insulating layer 252 of aluminum oxide

The insulating layer 252 can be composed of materials other than aluminum oxide, such as a glass material. Also, the insulating layer 251 does not have to correspond to the inner protrusions 222a and 232a. A comparable result is obtained, for example, when the width of the band of the insulating layer 251 in Fig.22 is expanded so as to include the area corresponding to the discharge gap D_1 .

In addition to the first embodiment, the third embodiment is also compatible with the second embodiment and any of the variations 1-1~1-12 and 2-1~2-13. According to the third embodiment, it is also possible to form a magnesium oxide layer and an aluminum oxide layer directly on the display electrodes 22 and 23 in the same manner as the insulating layer 25, without forming a dielectric layer 24 composed of a dielectric glass material.

<Methods of Manufacturing a PDP>

What follows is an explanation of the methods of manufacturing the PDP of the first, second, and third embodiments and the variations 1-1~1-12 and 2-1~2-13.

1. Manufacture of the Front Panel

Display electrodes 22 and 23 are formed on a surface of a front panel glass 21 composed of soda lime glass 2.6 mm thick.

Transparent electrodes (i.e. the snaking electrodes 220 and 230 and the isolated electrodes 222 and 232 of the embodiments discussed above) are the first to be formed using the following photo-etching process.

A photo-resist (e.g. an ultraviolet light curing resin) is coated over the entire surface of the front panel glass 21 at a thickness of $0.5\mu\text{m}$. A photomask of a predetermined pattern is then layered on top and ultraviolet light is illuminated, the non-solidified resin being washed away in a processing liquid bath. Then, using a CVD method (chemical evaporation method), the gaps in the resist on the front panel glass 21 are coated with ITO or a similar material used for making transparent electrodes. The snaking electrodes 220 and 230 and isolated electrodes 222 and 232, having a predetermined shape, are obtained by removing the resist using a washing liquid.

Next, bus lines having a thickness of $4\mu\text{m}$ and a width of $30\mu\text{m}$ are formed using a metal, a main component of which is either silver (Ag) or Cr-Cu-Cr. A screen-printing method is used when the bus lines are composed of silver and an evaporation method or sputtering method is used when the bus lines are composed of Cr-Cu-Cr. The same photo-etching method can be used when the display electrodes 22 and 23 are composed entirely of silver. A dielectric layer 24 is then formed by firing the front panel glass 21 after the entire surface thereof has been coated

with a lead glass paste at a thickness of 15-45 μm , covering over the display electrodes 22 and 23.

Next, an insulating layer 25 having a thickness of 0.3-0.6 μm is formed on the surface of the dielectric layer 24 using an evaporating method, a CVD method, or a similar method. The insulating layer 25 is usually composed of magnesium oxide (MgO). However, when sections of the insulating layer are composed of a different material (e.g. the combined use of magnesium oxide and aluminum oxide in the third embodiment), the insulating layer 25 is formed by a patterning process using an appropriate metal mask. This completes the manufacturing process of the front panel 20.

2. Manufacture of the Back Panel

Address electrodes 28 having a thickness of 5 μm are formed by using a screen-printing method to coat a conductive material composed mainly of silver in regularly spaced strips on a surface of the back panel glass 27 composed of soda lime glass 2.6mm thick. The gap between two adjacent address electrodes 28 is set at 0.4mm or less so as to make the PDP 2 of the present invention compatible with a 40-inch class NTSC method or a VGA method.

A dielectric film 29 is then formed by firing the back panel glass 27 arranged with address electrodes 28 after the

entire surface thereof has been applied with a lead glass paste 20~30 μm thick. Next, barrier ribs 30 of a height of 60~100 μm are formed on the dielectric film 29 in the gap between two adjacent address electrodes 28 using the same lead glass material as applied for the dielectric film 29. The barrier ribs 30 can be formed, for example, by repeatedly screen-printing a paste that includes the glass material mentioned above, before the firing process. The phosphor layers 31~33 are then formed by drying and firing the back panel glass 27 after a red (R), green (G), and blue (B) phosphor ink has been coated onto the wall surface of the barrier ribs 30 and the surface of the dielectric film 29 laying between two adjacent barrier ribs (30). Phosphor material commonly used in the manufacture of PDPs is as follows:

Red phosphors: $(Y_xGd_{1-x})\text{BO}_3:\text{Eu}^{3+}$

Green phosphors: $\text{Zn}_2\text{SiO}_4:\text{Mn}$

Blue phosphors: $\text{BaMgAl}_{10}\text{O}_{17}:\text{Eu}^{3+}$ (or $\text{BaMgAl}_{14}\text{O}_{23}:\text{Eu}^{3+}$)

The phosphor material can be a powder having an mean particle size of 3 μm . While there are several methods of applying the phosphor ink, the method used in the given example involves emitting phosphor ink from an extremely fine nozzle while forming a meniscus (a bridge generated by surface tension). Using this method the phosphor ink is applied evenly to the specified area. Other methods such as the screen-printing

method can be employed instead. This completes the manufacturing process of the back panel 26.

While the front panel glass 21 and the back panel glass 27 were described above as being composed of soda lime glass, this was simply by way of example and other materials can be used.

3. Completing the PDP

The front panel 20 and back panel 26 are adhered together using an adhesive glass. A high vacuum (8×10^{-4} Pa) is created within the discharge space 38, and the discharge space 38 is then filled at a predetermined pressure (approx. 266×10^3 Pa according to the given example) with a discharge gas, a main component of which is either Ne-Xe, He-Ne-Xe, or He-Ne-Xe-Ar. Experiment results show that the illuminance efficiency is improved when the pressure of the gas at the time of insertion is within a $1 \times 10^5 \sim 5.3 \times 10^5$ Pa range.

<Related Matters>

The present invention is described above using examples that are compatible with a gas discharge panel (PDP). However, the present invention can also be applied for use in other devices (gas discharge devices) apart from gas discharge panels. The construction shown in Fig.23 is an example of one such gas

discharge device. In the gas discharge device 400 shown in Fig.23(a), glass covers 401a and 401b, which have semi-circular cylindrical outer shells, cover both surfaces of a substrate 401, which is arranged on one surface with display electrodes 422 and 423 (Y electrode 422, X electrode 423). The glass covers 401a and 401b are adhered to the substrate 401 and the space within is then filled with a discharge gas. Discharge is generated within the discharge gas when a voltage is applied to the display electrodes 422 and 423. As shown in Fig.23(b), each of the display electrodes 422 and 423 have electrode prongs 4220 and 4230 formed in a ctenidium pattern, and the display electrodes 422 and 423 are arranged so as to extend across the electrode prongs 4220 and 4230. The electrode prongs 4220 4230 are electrode bases (or bus lines) upon which the inner protrusions 232a and outer protrusions 232b can be suitably arranged. The present invention is applicable to the display electrodes 422 and 423 of the gas discharge device 400 and similar gas discharge devices.

INDUSTRIAL APPLICABILITY

The gas discharge panel of the present invention can be used, for example, as a display panel for a television receiver.

ABSTRACT

A gas discharge panel having (a) a plurality of cells arranged in a matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of substrates, and (b) plural pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix, image display being generated by a discharge fired between the plural pairs of display electrodes. Each pair of display electrodes comprise (a) two bus lines lying parallel to each other and extending in the row direction of the matrix, (b) one or more inner protrusions arranged within each cell on an inner side of one or both of the bus lines so as to protrude toward an inner side of an opposite bus line, and (c) one or more outer protrusions arranged so as to protrude from an outer side of one or both of the bus lines. A shortest gap between each pair of display electrodes is either the gap between one of the bus lines and the inner protrusions provided on the opposite bus lines or the gap between the inner protrusions provided on both of the bus lines. By concentrating the electric charge within the shortest gap during the discharge period, it is possible to keep the discharge firing voltage below existing levels. Also, the generated discharge gradually expands to the outer protrusions, allowing a sustain discharge (surface discharge) to be secured over a wide area. Thus the

present invention allows for an excellent discharge capacity to be achieved while improving the illuminance efficiency above existing levels. It is also possible, according to the present invention, to arrange the inner protrusions on each of the bus lines so that the ends are out of alignment along the row direction of the matrix.

In summary, the excellent discharge capacity and improved illuminance efficiency achieved by the present invention is due to the favorable way in which the discharge capacity expands along the row and column directions of the matrix (i.e. parallel to the surface of the substrates) for the period that the discharge is being sustained between the plural pairs of display electrodes.

CLAIMS

1. A gas discharge panel having (a) a plurality of cells arranged in a matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of substrates, and (b) plural pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix, each pair of display electrodes comprising:

two bus lines, being parallel to each other and extending in the row direction of the matrix;

one or more inner protrusions, being arranged within each cell on an inner side of one or both of the bus lines so as to protrude toward an inner side of an opposite bus line; and

one or more outer protrusions, being arranged so as to protrude from an outer side of one or both of the bus lines.

2. The gas discharge panel of claim 1, wherein a relation $P_e = A \times P_s / n$ is satisfied in relation to the two bus lines, P_e being a pitch of either the inner or outer protrusions, P_s being a pitch of the cells along the row direction of the matrix, A being a positive value less than 1, and n being a natural number.

3. The gas discharge panel of claim 1, wherein the bus lines are composed of a metal and the inner and outer protrusions are composed of a transparent electrode material.

electrodes is covered with an insulating layer, an area of the insulating layer that corresponds to a shortest discharge gap being composed of magnesium oxide and a remaining area thereof being composed of a material having a lower electron emission rate than magnesium oxide.

9. The gas discharge panel of claim 8, wherein the material having a lower electron emission rate than magnesium oxide is aluminum oxide.

10. The gas discharge panel of claim 1, wherein the inner protrusions are provided on each of the two bus lines, the ends of the inner protrusions arranged on each of the bus lines being out of alignment along the row direction of the matrix.

11. The gas discharge panel of claim 10, wherein a relation $P_e = A \times P_s / n$ is satisfied in relation to the two bus lines, P_e being a pitch of either the inner or outer protrusions, P_s being a pitch of the cells along the row direction of the matrix, A being a positive value less than 1, and n being a natural number.

12. The gas discharge panel of claim 10, wherein the inner protrusions have squared ends along the row direction of the matrix, the squared ends of any two closest facing inner

protrusions being out of alignment such that a width in the row direction of the matrix of a section of the squared ends that face each other is $10\mu\text{m}$ or less.

13. The gas discharge panel of claim 10, wherein the inner protrusions have tapered ends along the row direction of the matrix, the tapered ends of any two closest facing inner protrusions being out of alignment by $10\mu\text{m}$ or more along the row direction of the matrix.

14. The gas discharge panel of claim 10, wherein a plurality of barrier ribs are formed between the pair of substrates along a column direction of the matrix, at least a section of the inner protrusions overlapping with the barrier ribs.

15. The gas discharge panel of claim 10, wherein the outer protrusions extend in a column direction of the matrix, a surface area of each of the outer protrusions being greater than a surface area of each of the inner protrusions.

16. The gas discharge panel of claim 10, wherein a width of each of the outer protrusions along the row direction of the matrix is wider as the distance from the bus line increases.

17. The gas discharge panel of claim 10, wherein a shape of the inner protrusions arranged on each of the bus lines is different.

18. The gas discharge panel of claim 10, wherein a shortest discharge gap between the plural pairs of display electrodes corresponds to a minimum discharge firing voltage or a voltage in a vicinity thereof as shown on a Paschen curve plotting a relationship between a Pd product and a discharge firing voltage, P being a pressure of the discharge gas and d being a discharge gap.

19. The gas discharge panel of claim 10, wherein the inner surface of the substrate arranged with the plural pairs of display electrodes is covered with an insulating layer, an area of the insulating layer that corresponds to a shortest discharge gap being composed of magnesium oxide and a remaining area thereof being composed of a material having a lower electron emission rate than magnesium oxide.

20. The gas discharge panel of claim 19, wherein the material having a lower electron emission rate than magnesium oxide is aluminum oxide.

08689473.071704
10.12.2024

21. A gas discharge panel having (a) a plurality of cells arranged in a matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of substrates, and (b) plural pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix, each pair of display electrodes comprising:

two bases, being parallel to each other and extending in the row direction of the matrix; and

one or more inner protrusions, being arranged within each cell on an inner side of each of the bases so as to protrude toward an inner side of an opposite base, the ends of the inner protrusions arranged on each of the bases being out of alignment along the row direction of the matrix.

22. The gas discharge panel of claim 21, wherein a relation $P_e = A \times P_s / n$ is satisfied in relation to the two bus lines, P_e being a pitch of either the inner or outer protrusions, P_s being a pitch of the cells along the row direction of the matrix, A being a positive value less than 1, and n being a natural number.

23. The gas discharge panel of claim 21, wherein the inner protrusions have squared ends along the row direction of the matrix, the squared ends of any two closest facing inner

protrusions being out of alignment such that a width in the row direction of the matrix of a section of the squared ends that face each other is $10\mu\text{m}$ or less.

24. The gas discharge panel of claim 21, wherein the inner protrusions have tapered ends along the row direction of the matrix, the tapered ends of any two closest facing inner protrusions being out of alignment by $10\mu\text{m}$ or more along the row direction of the matrix.

25. The gas discharge panel of claim 21, wherein a plurality of barrier ribs are formed between the pair of substrates along a column direction of the matrix, at least a section of the inner protrusions overlapping with the barrier ribs.

26. The gas discharge panel of claim 21, wherein a shape of the inner protrusions arranged on each of the bases is different.

27. The gas discharge panel of claim 21, wherein a shortest discharge gap between the plural pairs of display electrodes corresponds to a minimum discharge firing voltage or a voltage in a vicinity thereof as shown on a Paschen curve plotting a relationship between a Pd product and a discharge firing voltage, P being a pressure of the discharge gas and d being a discharge

gap.

28. A gas discharge panel having (a) a plurality of cells arranged in a matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of substrates, and (b) plural pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix, each pair of display electrodes comprising:

two bases, being extended in a row direction of the matrix and snaking along the plural pairs of display electrodes.

29. The gas discharge panel of claim 28, wherein a wavelength of each of the bases is out of alignment by half a wavelength.

30. The gas discharge panel of claim 28, wherein the plural pairs of display electrodes are arranged so that a bus line part composed of a metal and extending in a row direction of the matrix is connected electrically to each of the bases.

31. The gas discharge panel of claim 30, wherein the bases are composed of a transparent electrode material.

32. The gas discharge panel of claim 28, wherein the bases are

composed of a metal.

33. A gas discharge panel having (a) a plurality of cells arranged in a matrix, each cell being filled with a discharge gas which is enclosed between a facing pair of substrates, and (b) plural pairs of display electrodes arranged on an inner surface of one of the substrates so as to extend in a row direction of the matrix, each pair of display electrodes comprising:

two bus lines, being extended in the row direction of the matrix; and

two bases, being connected electrically to and snaking along the bus lines, at least a section of the bases being arranged so as to be separate between two adjacent barrier ribs.

34. A method of manufacturing a gas discharge panel including (a) a display electrode arranging step for arranging plural pairs of display electrodes on a main surface of a first substrate so as to extend in a row direction, (b) an insulating layer covering step for covering the first substrate with an insulating layer, and (c) a cell forming step for forming a plurality of cells in a matrix by arranging the main surface of the first substrate to face a main surface of a second substrate with a plurality of barrier ribs extending in a column

direction interposed therebetween, each cell being an area in which a pair of display electrodes extend across two adjacent barrier ribs,

wherein the display electrode arranging step has a substep for arranging two bus lines, which are parallel to each other and extend in a same direction, and for providing inner protrusions, which are arranged within each cell on an inner side of one or both of the bus lines, and

the insulating layer covering step has a substep for forming an insulating layer, an area corresponding to a shortest discharge gap between the plural pairs of display electrodes being composed of magnesium oxide and a remaining area thereof being composed of a material having a lower electron emission rate than magnesium oxide.

35. The gas discharge panel of claim 34, wherein the material used in the substep of the insulating layer covering step having a lower electron emission rate than magnesium oxide is aluminum oxide.

36. A method of manufacturing a gas discharge panel including (a) a display electrode arranging step for arranging plural pairs of display electrodes on a main surface of a first substrate so as to extend in a row direction, (b) an insulating

layer covering step for covering the first substrate with an insulating layer, and (c) a cell forming step for forming a plurality of cells in a matrix by arranging the main surface of the first substrate to face a main surface of a second substrate with a plurality of barrier ribs extending in a column direction interposed therebetween, each cell being an area in which a pair of display electrodes extend across two adjacent barrier ribs,

wherein the display electrode arranging step sets a shortest discharge gap between the plural pairs of display electrodes according to a minimum discharge firing voltage or a voltage in a vicinity thereof as shown on a Paschen curve plotting a relationship between a Pd product and a discharge firing voltage, P being a pressure of the discharge gas and d being a discharge gap.

37. A method of manufacturing a gas discharge panel including (a) a display electrode arranging step for arranging plural pairs of display electrodes on a main surface of a first substrate so as to extend in a row direction, (b) an insulating layer covering step for covering the first substrate with an insulating layer, and (c) a cell forming step for forming a plurality of cells in a matrix by arranging the main surface of the first substrate to face a main surface of a second

substrate with a plurality of barrier ribs extending in a column direction interposed therebetween, each cell being an area in which a pair of display electrodes extend across two adjacent barrier ribs,

wherein the display electrode arranging step has a substep for arranging two bus lines, which are parallel to each other and extend in a same direction, and for providing inner protrusions, which are arranged within each cell on an inner side of one or both of the bus lines, the inner protrusions being provided in the substep so as to satisfy a relation $P_e = A \times P_s / n$, P_e being a pitch of either the inner or outer protrusions, P_s being a pitch of the cells along the row direction of the matrix, A being a positive value less than 1, and n being a natural number.

38. A gas discharge device having one or more pairs of electrodes arranged to face a discharge space filled with a discharge gas, wherein a voltage is applied to each of the electrodes so as to fire a discharge between the one or more pairs of electrodes and generate illumination, each pair of electrodes comprising:

two electrode bases, being extended in a same direction;
one or more inner protrusions, being arranged on an inner side of one or both of the electrode bases so as to protrude toward an inner side of an opposite electrode base; and

one or more outer protrusions, being arranged so as to protrude from an outer side of one or both of the electrode bases.

39. The gas discharge panel of claim 38, wherein each pair of electrodes has two electrode bases that extend in a same direction and snake along the one or more pairs of electrodes.

40. The gas discharge panel of claim 38, wherein the ends of the inner protrusions arranged on each of the electrode bases are out of alignment.

41. The gas discharge panel of claim 40, wherein each pair of electrodes has two electrode bases that extend in a same direction and snake along the one or more pairs of electrodes, a wavelength of each of the electrode bases being out of alignment.

ABSTRACT OF THE DISCLOSURE

A gas discharge panel to increase the illuminance efficiency and a method of manufacturing includes providing a plurality of cells arranged in a matrix between a pair of substrates. Pairs of display electrodes are arranged on an inner surface of one of the
5 substrates and include two bus lines lying parallel to each other with one or more inner protrusions arranged within each cell relative to the bus lines. This arrangement provides a relatively short discharge gap between the pair of display electrodes.




Fig. 2









Fig. 3




















Fig. 11






Fig. 13









Fig. 17






Fig. 19





Fig. 20






Fig. 23







Fig. 24



Docket No.

NAK1-BP44

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

GAS DISCHARGE PANEL, GAS DISCHARGE DEVICE, AND RELATED METHODS
OF MANUFACTURE

the specification of which

(check one)

☐ is attached hereto.

☒ was filed on 21/01/00 as United States Application No. or PCT International
Application Number PCT/JP00/00281
and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

11-14801	Japan	22/01/99	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	
11-81132	Japan	25/03/99	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	
11-367660	Japan	24/12/99	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

Joseph W. Price, Reg. No. 25,124
 Albin H. Gess, Reg. No. 25,726
 Franklin D. Ubell, Reg. No. 27,009

Doyle B. Johnson, Reg. No. 39,240
 Michael J. Moffatt, Reg. No. 39,304
 Bradley D. Blanche, Reg. No. 38,387

Send Correspondence to: Joseph W. Price
PRICE, GESS & UBELL
2100 S.E. Main St., Ste. 250
Irvine, CA 92614

Direct Telephone Calls to: (name and telephone number)
Joseph W. Price, 949/261-8433

Full name of sole or first inventor		<u>Ryuichi MURAI</u>
Sole or first inventor's signature		<u>Ryuichi Murai</u>
		Date
		<u>July 9, 2001</u>
Residence		
<u>4-4-67-105, Kamishinden, Toyonaka-shi, Osaka 565-0085 Japan JPY</u>		
Citizenship		
<u>Japan</u>		
Post Office Address		
<u>same as residence</u>		

Full name of second inventor, if any		<u>Yuusuke TAKADA</u>
Second inventor's signature		<u>Yuusuke Takada</u>
		Date
		<u>July 9, 2001</u>
Residence		
<u>1-10-319, Ikuno, Katano-shi, Osaka 576-0054 Japan JPY</u>		
Citizenship		
<u>Japan</u>		
Post Office Address		
<u>same as residence</u>		

300 Full name of third inventor, if any Akira SHIOKAWA

Third inventor's signature Akira Shio/awa

Date

July 9, 2001

Residence

-7-8, Shoji, Ikuno-ku, Osaka-shi, Osaka 544-0002 Japan JPX

Citizenship
Japan

Post Office Address

same as residence

400 Full name of fourth inventor, if any Hiroyosi TANAKA

Fourth inventor's signature

Hiroyosi Tanaka

Date

July 9, 2001

Residence

288-3, Kiyomizu 1-chome, Higashiyama-ku, Kyoto-shi Kyoto JPX

Citizenship 605-0862 Japan
Japan

Post Office Address

same as residence

Full name of fifth inventor, if any

Fifth inventor's signature

Date

Residence

Citizenship

Post Office Address

Full name of sixth inventor, if any

Sixth inventor's signature

Date

Residence

Citizenship

Post Office Address